

# VT03211D-P1-S2

Dahua IP domofon VT03211D-P1-S2 qapı zəngi; 2 MP; Bucaq - 129°; 120dB; IP65 IK08; Qara; Metal; PoE; IC Card: 10000;



## Specifications

Model	VT03211D-P1-S2
Brand	Dahua
Başlantı tipi	IP
Cihaz	Zəng
PoE	PoE
Yaddaş	SD Card
Material	Metal

## KEY FEATURES

System	
Main Processor	Embedded processor
Operating System	Embedded Linux operating system
Button Type	Mechanical
Interoperability	ONVIF
Network Protocol	SIP; P2P; IPv4; DNS; RTSP; RTP; TCP; UDP
Basic	
Camera	1/2.8" 2MP CMOS high definition, low illumination/WDR/color/IR
Angle of View	Horizontal: 129°; vertical: 74°; diagonal: 147°
WDR	120dB
Noise Reduction	3D noise reduction
Video Compression	H.264
Video Resolution	Main stream: WVGA, 720P, D1 Sub stream: CIF, WVGA, QVGA, 1080P, D1
Frame Rate	PAL: 25 fps NTSC: 30 fps
Video Bit Rate	256K to 4M
Light Compensation	Auto IR
D/N	ICR auto switch
Audio Compression	G.711Mu; G.711u; PCM
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression and cancellation/digital noise reduction
Audio Bit Rate	16KHz, 16Bit
Function	
Communication	Full digital
Unlock Mode	Card/App/indoor monitor unlock
Card Type	IC card
Motion Detection	Video Motion Detection
Auto Snapshot	Auto snapshot can only be enabled on indoor monitors
Leave Photos and Messages	Yes (Insert an SD card into the indoor monitor.)
Web Configuration	Yes
Performance	
Card Reading Distance	3cm–5cm
Casing	PC+Aluminum alloy, metal frame
Capacity	
Card Capacity	10,000
Port	
RS-485	1
Electric Lock	1
Alarm Input	1
Alarm Output	1

---

<b>Exit Button</b>	<b>1</b>
<b>Door Status Detection</b>	<b>1</b>
<b>Lock Control</b>	<b>1, normally closed by default</b>
<b>Network</b>	<b>1 10Mbps/100Mbps network port</b> <b>(8-core white ribbon cable)</b>
<b>Alarm</b>	
<b>Tamper Alarm</b>	<b>Yes</b>
<b>General</b>	
<b>Color</b>	<b>Greyish-black</b>
<b>Power Supply</b>	<b>12V DC 1A</b> <b>Standard PoE</b>
<b>Installation</b>	<b>Surface mount</b>
<b>Certifications</b>	<b>CE/FCC</b>
<b>Accessory</b>	<b>Alarm ribbon cable</b>
<b>Dimensions</b>	<b>181 mm×101 mm×31 mm (7.13" × 3.98" × 1.22")</b>
<b>Protection Grade</b>	<b>IP65</b> <b>(silicone sealant is needed, see the quick start guide)</b> <b>IK08</b>
<b>Operating Temperature</b>	<b>-30°C to + 60°C (-22°F to +140°F)</b>
<b>Operating Humidity</b>	<b>10%RH-95%RH (non-condensing)</b>
<b>Operating Environment</b>	<b>Outdoor</b>
<b>Operating Altitude</b>	<b>Beneath 3000 m (9842.51 ft)</b>
<b>Power Consumption</b>	<b>Standby≤1W, working≤7W</b>
<b>Gross Weight</b>	<b>660 g (5.51 lb)</b>