

CUDY

WR3600

Kod: 00-00005556 · Routerlər



Cudy WR3600 Gigabit Wi-Fi 7 Mesh Router BE3600 yeni nəsil Wi-Fi 7 texnologiyası ilə ultra sürətli və stabil internet təqdim edir. Mesh dəstəyi sayəsində geniş əhatə, aşağı gecikmə və çoxsaylı cihazların eyni anda problemsiz qoşulması mümkündür.

Texniki göstəricilər



WiFi7

WIFI



Dual band

Genişlik



Mesh

Mesh



2.4Ghz/5Ghz

Tezlik



1000 mb/s

Port sürəti



200+

Qoşulma sayı

Ətraflı məlumat

WR3600 1.0	
CPU Details	2.0 GHz Quad-Core, ARM Cortex-A7
Flash/ROM	128 MB (1 Gbit) NAND
DDR/RAM	512 MB (4 Gbit) DDR3L
5 GHz Wi-Fi Speed	2882 Mbps
2.4 GHz Wi-Fi Speed	688 Mbps
5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
Wi-Fi Antennas	4× Fixed
FEM or PA/LNA	• 5 GHz: 2× External • 2.4 GHz: 2× Internal
Beamforming	True
Range Performance	Max: 220 m (722 ft) Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
Wall Performance	Two wooden walls with thickness < 10 cm (4") One concrete wall with thickness < 20 cm (7") or two concrete walls with thickness < 10 cm (4")
Gigabit RJ45 Ports	5
Ethernet Notes	1× WAN port, the rest are LAN ports
LED	• Power • Internet • WAN • LAN • 2.4 GHz Wi-Fi • 5 GHz Wi-Fi

Physical Buttons	• WPS Button • Reset Button
Power Input	DC Jack
Power Methods	DC
DC Input	12V 1A
Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC Output: 12V 1A DC
Max Power Consumption (W)	9W
Environment	• Operating Temperature: 0 °C ~ 40 °C (32 °F ~ 104 °F) • Storage Temperature: -40 °C ~ 70 °C (-40 °F ~ 158 °F) • Humidity: 10% ~ 90% non-condensing • Storage Humidity: 5% ~ 95% non-condensing
FCC, CE	
Installation	• Desktop • Wall-mount
Dimension	Device: 183.3×109×38 mm 7.22×4.29×1.5 inches Each Antenna: 175 mm 6.89 inches
Product Weight	333.5 g (11.76 oz.)
• WR3600 • Power Adapter • Ethernet Cable • Installation Guide	
Retail Package Weight	ZH: 725.0 g (25.57 oz.)
Retail Package Dimension	330×256×60 mm 12.99×10.08×2.36 inches
Units per Carton	10

Carton Dimension	52.8×31.7×34.7 cm 20.79×12.48×13.66 inches
Carton Gross Weight	ZH: 8.1 kg (17.86 lbs)
Carton Net Weight	ZH: 7.3 kg (16.09 lbs)
Wi-Fi Standards	Wi-Fi 7
Max Wi-Fi Modulation	4K-QAM
Wi-Fi Efficiency	• MLO • MRU • Puncturing • OFDMA • MU-MIMO • BSS Color
Max Capacity	512
Recommended Client Upper Limit	200
Max Wi-Fi Channel Width	160 MHz
Wi-Fi Security	WPA/WPA2/WPA3
Guest Network	2.4 GHz, 5 GHz
WPS	True
Operation Modes	• Wi-Fi Router • Access Point • Range Extender
Mesh	Cudy Mesh
Mesh Backhaul	• Wireless Backhaul • Wired Backhaul
Multi-Band Backhaul	True

WAN Mode	• DHCP • Static IP • PPPOE • PPTP • L2TP
Notes	The Range Extender/WISP/Client modes will be available with later firmware upgrade. Cudy Mesh and related backhaul features will be available with later firmware upgrade.
QoS	Per-User Rate Limiting
DHCP	• Address Reservation • DHCP Client List • Server
IP Versions	IPv4/IPv6
IPv6 Protocols	• Relay • Dynamic (SLAAC/DHCPv6) • Static (Fixed IP) • Passthrough • 464XLAT • MAP-E • DS-Lite
IPTV/VLAN	• Bridge • Tag VLAN • VoIP VLAN • IPTV VLAN
TTL Customization	• Extend • Spoof • Custom
IGMP	• IGMP Proxy • IGMP Snooping

Forwarding	• Port Forwarding • Port Triggering • UPnP • DMZ
Firewall	• SPI Firewall • DoS Protection • Block PING
Application Layer Gateway	• IPSec Passthrough • L2TP Passthrough • PPTP Passthrough • FTP Passthrough • TFTP Passthrough • H323 Passthrough • SIP Passthrough • RTSP Passthrough
VPN Server	• WireGuard • OpenVPN • IPsec • Zerotier • PPTP • L2TP
VPN Client	• WireGuard • OpenVPN • IPsec • Zerotier • PPTP • L2TP
VPN Performance	• OpenVPN Client (UL/DL): 66 / 66 Mbps • OpenVPN Server (UL/DL): 65 / 64 Mbps • WireGuard Client (UL/DL): 150 / 223 Mbps • WireGuard Server (UL/DL): 251 / 177 Mbps

DNS Options	• DNS over TLS • Manual DNS • Rebind Protection • Override Clients' DNS
DNS over TLS Providers	• Cloudflare • Google • Quad9 • Custom
Wake on LAN	True
Online Detection	True
Parental Controls	• Profiles Settings • Offline Time • Online Time • Pause the Internet • Web Filter
All Devices Management	• Wi-Fi Time Schedule • MAC Filter • IP/MAC Binding
Per-Devices Management	• Internet On/Off • VPN On/Off • Online Time Schedule • Device Rename
Content Management	• Domain Filter • IP Filter
LED Control	True
Local Control Method	• Config Web Page • App Control
Remote Control Method	• Config Page via HTTPS • App Control • TR069/TR098/TR111/TR143/TR181

Firmware Upgrade	• Local Update • App (Over the Air) • Online Update
Reliability	• Timed Reboot • Backup and Restore
Diagnostic Tools	• Diagnosis • Ping • Traceroute • NSLookup • System Log

Languages	• English • Bengali • Catalan • Czech • German • Greek • Spanish • French • Hebrew • Croatian • Hungarian • Italian • Japanese • Khmer • Korean • Dutch • Norwegian • Polish • Portuguese • Romanian • Russian • Slovak • Swedish • Thai • Turkish • Ukrainian • Vietnamese • Simplified Chinese • Traditional Chinese
-----------	--

Panel	• Internet Status • Mesh Status • Devices Management • WAN Status • LAN Status • Wi-Fi Status • VPN Status • DHCP Server Status • System Version
Charts	• Internet Speed • Wi-Fi Speed • Mesh Topology

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az