TP-LINK

XC220-G3V

Kod: 00-00004440 · Routerlər



TP-Link XC220-G3V AC1200 GPON router, yüksək sürətli Wi-Fi, 4x Gigabit LAN, VoIP dəstəyi və sabit GPON bağlantısı ilə ev və kiçik ofislər üçün ideal seçimdir. IPTV, IP telefoniya və sürətli interneti bir cihazda təqdim edir, asan idarəetmə və təhlükəsizlik funksiyaları ilə seçilir.

Texniki göstəricilər

GPON Tip	**Dual band** Genişlik
1000 mb/s Port sürəti	**WiFi5** WIFI
2.4Ghz/5Ghz Tezlik	

Ətraflı məlumat

HARDWARE FEATURES	
External Power Supply	12V/1.0A
Interface	4 10/100/1000 Mbps RJ45 LAN Ports 1 SC/APC GPON Port 1 RJ11 FXS Port
Button	Power On/Off Button, WPS/Wi-Fi Button, RESET Button
Antenna	2 External Dual Band Antennas

WIRELESS FEATURES	
Frequency	2.4 GHz and 5 GHz (not Supports DFS)
Signal Rate	867 Mbps on 5 GHz, 300 Mbps on 2.4 GHz
Transmit Power	2.4 GHz: 26 dBm(EIRP), 5GHz: 27dBm (EIRP)
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Wireless Standards	IEEE 802.11ac/n/a 5 GHz, IEEE 802.11b/g/n 2.4 GHz
Wireless Schedule	Support 2.4 GHz and 5 GHz Wireless Schedule
Mesh Technology	EasyMesh Compatible, TP-Link OneMesh

SOFTWARE FEATURES	
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port Forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Quality of Service	Hardware QoS
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec Pass-through
Management	Web Based Configuration(HTTP), Remote management, Command Line Interface, SSL for TR-069, Web Based Firmware Upgrade, Diagnostic Tools, OMCI

SOFTWARE FEATURES	
Security	NAT Firewall, Access Control, MAC/IP/URL Filtering, IP and MAC Address Binding, Defense “Denial of Service (DoS), SYNFlooding, Ping of Death”
Advanced Functions	Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, DNS Relay, DDNS, IGMP V1/V2/V3
Protocols	Supports IPv4 and IPv6
VOIP Features	Call hold, Call forward, Warm call, Do not disturb, Call restriction, Speed dial, etc. Caller ID, 3-party conference, SIP account – up to 8 accounts

OTHERS	
Package Contents	AC1200 Wireless VoIP GPON Router RJ45 Ethernet Cable Power Adapter Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
Environment	Operating Temperature: 0℃~40℃ (32℉ ~104℉) Storage Temperature: -40℃~70℃ (-40℉ ~158℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az