

# XL-3620S

## SUNLUX XL-3620S WIRED 2D BARCOD SCANNER



Model	XL-3620S
Brend	Sunlux
Növ	Skaner
Printerin tipi	Barkod
Skaner qoşulma	USB

## Specification

Image Sensor	CMOS
Light Levels	White LED (Lighting) RED aiming light
CPU	32bit ARM
IP Standard	IP 54
Image Sensor	640x480 pixels
Scanning Speed	60fps
Decoding Depth	60~360mm (13milPCS90%)
Minimum Resolution	3mil
Motion Tolerance	13cm / second,(Skew/Pitch) +/- 65°
Interface	USB-HID, USB-VCP, RS232
Scan Mode	Manual & Automatic
Materials	ABS+TPU
Size	L*W*H : 112.5*81.5*204(mm)
Weight	185g
Input Voltage	DC 3.6V ~ 5.5V
Working Current	142mA
Stand-by Current	42mA
Temperature(Operating)	-10°C ~ 50°C
Temperature(Storage)	-20°C ~ 60°C
Indicate	LED Indicator and Buzzer
Cable Standard	2 Meters

Humidity	5% ~ 95%(non-condensing)
Light Source	0 ~ 5000Lux(fluorescent light),0 ~ 100,000Lux(daylight)
Decoding Capability	1D: Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5,Matrix 2 of 5, Code93, Code128, GS1-128,UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded,etc. 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code