TP-LINK

XN021-G3

Kod: 00-00004476 · Routerlər



TP-Link XN021-G3 (ES) XPON şəbəkə texnologiyası ilə işləyən çoxfunksiyalı routerdir. Bu cihaz eyni anda həm fiber-optik internet, həm də kabel televiziyası (CATV) xidmətlərini dəstəkləyir. 300Mbps simsiz sürət və 4 ədəd Gigabit LAN portu ilə evdəki bütün cihazlar üçün mükəmməl sürət və stabil əlaqə təmin edir.

Texniki göstəricilər

GPON	**2.4Ghz**
Tip	Tezlik
1000 mb/s	**WiFi4**
Port sürəti	WIFI

Ətraflı məlumat

HARDWARE FEATURES	
External Power Supply	9V/0.6A
Interface	1× 10/100/1000 Mbps RJ45 LAN Port 1× 10/100 Mbps RJ45 LAN Port 1× CATV Port 1× PON Port
Button	RESET Button
Antenna	2× External Antennas
Data Rates	Downstream Speeds: 2.488 Gbps (GPON), 1.25 Gbps (EPON) Upstream Speeds: 1.244 Gbps (GPON), 1.25 Gbps (EPON)§

WIRELESS FEATURES	
Frequency	2.4 GHz
Signal Rate	Up to 300 Mbps
Transmit Power	CE: < 20 dBm
Wireless Functions	Enable/Disable Wireless Radio, WMM, Wireless Statistics
Wireless Security	WPA/WPA2/WPA3 Encryptions
Wireless Standards	IEEE 802.11b/g/n 2.4 GHz
Wireless Schedule	Support 2.4 GHz Wireless Schedule

SOFTWARE FEATURES	
DHCP	Server, Client, DHCP Client List, Address Reservation, DHCP Relay
Port Forwarding	Virtual Server, Port Triggering, DMZ, ALG, UPnP
Quality of Service	WMM
Dynamic DNS	DynDns, NO-IP
Management	Local management: WebGUI management Remote management: OMCI, TR-069, TR-098, TR-143

SOFTWARE FEATURES	
Security	SPI Firewall, DDoS, Access Control, IP-MAC binding
Advanced Functions	Parental Controls, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, DNS Relay, DDNS, IPTV Support, IGMP V2/3 and IGMP Snooping/Proxy
Protocols	IPv4, IPv6

OTHERS	
Package Contents	1× XPON Router XN021-G3 1× RJ45 Ethernet Cable 1× Power Adapter 1× Quick Installation Guide
System Requirements	Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Subscription with an internet service provider (for internet access)
Environment	Operating Temperature: 0℃–40℃ (32℉–104℉) Storage Temperature: -40℃–60℃ (-40℉–140℉) Operating Humidity: 10%–90% non-condensing Storage Humidity: 5%–90% non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az