

# XP-350B

## XPRINTER XP-350B THERMAL LABEL PRINTER (barcod)



Model	XP-350B
Brend	Xprinter
Növ	Printer
Printerin tipi	Barkod
Printer qoşulma	USB

## Specification

Model	XP-350B	XP-350BM
Printing Features		
Resolution	203 DPI (8 dots/mm)	
Printing method	Direct Thermal	
Max.print speed	152mm/s Max.	
Max.print width	Max.76 mm	
Media		
Media type	Thermal paper/Thermal stickers paper	
Media width	20~82 mm	
Media thickness	0.06~0.19 mm	
Media roll diameter	Max.100 mm	
Performance Features		
Memory	DRAM:4M FLASH:4M	
Interfaces	USB+Serial	USB+Serial+Lan
Sensors	Print head temperature sensor / Cover open / Paper end / Gap	
Drawer port	1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies		
Character sizes	Font 0 to Font8	
1D barcode	CODE128 EAN128 ITF CODE39 CODE39C CODE39S CODE93 EAN13 EAN13+2 EAN13+5 EAN8 EAN8+2 EAN8+5 CODABAR POSTNET UPC-A UPCA+2 UPCA+5 UPCE UPCE+2 UPCE+5 MSI MSIC PLESSEY ITF14 EAN14	

2D bar code	PDF417, QR CODE, DATMATRIX
Emulaion	TSPL, ESC/POS
Physical Features	
Dimension	220*148*150mm (D*W*H)
Weight	1.44 kg
Reliability	
Print head life	100 km
Software	
Driver	Windows
Power supply	
Input	DC 24V/2.5A
Environmental Conditions	
Operation	5~45 Humidity:RH 20~80%
Storage environment	-40~55 Humidity: RH :≤93% (40)