

XP-350B

XPRINTER XP-350B THERMAL LABEL PRINTER (barcod)



Specifications

Model	XP-350B
Brand	Xprinter
Növ	Printer
Printerin tipi	Barkod
Printer qoʻulma	USB

KEY FEATURES

Model XP-350B XP-350BM

Printing Features

Resolution 203 DPI (8 dots/mm)

Printing method Direct Thermal

Max.print speed 152mm/s Max.

Max.print width Max.76 mm

Media

Media type Thermal paper/Thermal stickers paper

Media width 20~82 mm

Media thickness 0.06~0.19 mm

Media roll diameter Max.100 mm

diameter

Performance Features

Memory DRAM:4M FLASH:4M

Interfaces USB+Serial USB+Serial+Lan

Sensors Print head temperature sensor / Cover open / Paper end / Gap

Drawer port 1 ports (Pin 2 for cashdrawer)

Fonts/Graphics/Symbologies

Character sizes Font 0 to Font8

1D barcode CODE128, EAN128, ITF, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14

2D bar code PDF417, QR CODE, DATMATRIX

Emulaion TSPL, ESC/POS

Physical Features

Dimension 220*148*150mm (D*W*H)

Weight 1.44 kg

Reliability

Print head life 100 km

Software

Driver Windows

Power supply

Input DC 24V/2.5A

Environmental Conditions

Operation 5~45 Humidity:RH 20~80%

Storage environment -40~55 Humidity: RH :≤93% (40)