

XP-80K

XPRINTER RECEIPT XP-80K USB+LAN



Model	XP-80K
Brend	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoşulma	USB+LAN

Specification

Printing		
Printing method	Direct thermal	
Media width	79.5±0.5mm / φ 80 mm	
Print width	72mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	230mm/s	260mm/s
Interface	USB / USB+Serial / USB+Lan / (Optional: Bluetooth/Wifi)	USB+Serial+Lan (Optional: Bluetooth/Wifi)
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK Font A: 1.5×3.0mm 12×24 dots Font B: 1.1×2.1mm 9×17 dots Chinese, traditional Chinese: 3.0×3.0mm 24×24 dots	
Barcode Character		
Extension character sheet	PC437 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranI Latvian Arabic PT151 1251	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	96 Kbytes: USB+Serial / USB 256 Kbytes: USB+Lan	256 Kbytes
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100V/240V, 50/60Hz; Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		

Weight	0.89 KG
Dimensions	168 × 130 × 123.5mm(D×W×H)
Environmental Requirements	
Work environment	Temperature(0~45℃) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~90%)
Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC / POS
Driver	Windows / Linux / Mac OS / Android