

XP-80K

XPRINTER RECEIPT XP-80K USB+LAN



Model	XP-80K
Brend	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoşulma	USB+LAN

Specification

Printing		
Printing method	Direct thermal	
Media width	79.5±0.5mm / φ 80 mm	
Print width	72mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	230mm/s	260mm/s
Interface	USB / USB+Serial / USB+Lan / (Optional: Bluetooth/Wifi)	USB+Serial+Lan (Optional: Bluetooth/Wifi)
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK:Font A:1.5×3.0mm:12×24 dots:Font B:1.1×2.1mm:9×17 dots:Chinese,traditional Chinese:3.0×3.0mm:24×24 dots:	
Barcode Character		
Extension character sheet	PC437:Standard Europe:Katakana:PC850:Multilingual:PC860:Portuguese:PC863:Canadian-French:PC865:Nordic:West Europe:Greek:Hebrew:East Europe:Iran:WPC1252:PC866:Cyrillic#2:PC852:Latin2:PC858:Iran:Latvian:Arabic:PT151:1251:	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	96 Kbytes: USB+Serial / USB 256 Kbytes: USB+Lan	256 Kbytes
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100V/240V, 50/60Hz; Output:DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	0.89 KG	
Dimensions	168 × 130 × 123.5mm(D×W×H)	
Environmental Requirements		
Work environment	Temperature(0~45) humidity(10~80%)	
Storage environment	Temperature(-10~60) humidity(10~90%)	

Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC / POS
Driver	Windows / Linux / Mac OS / Android