

XP-D230H

Xprinter XP-D230H — yüksək performanslı termal etiket printeridir. USB və Ethernet bağlantısı sayəsində şəbəkəyə asan integrasiya olunur. Sürətli və səssiz çap, 203 dpi qətnamə və müxtəlif etiket ölçülərini dəstəkləyir. Mağaza, logistika və anbar sistemləri üçün mükəmməldir.



Specifications

Model	XP-D230H
Brand	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qo?ulma	USB+LAN

KEY FEATURES

Model	XP-D230H
Printing	
Printing method	Direct thermal
Paper width	58±0.5mm / 79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line(adjustable by command)
Printing speed	230 mm/s Max.
Interface	USB/LanOptional : WIFI/Bluetooth)
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANKFont A1.5×3.0mm12×24 dotsFont B1.1×2.1mm9×17 dotsChinese,traditional Chinese:3.0×3.0mm24×24 dots
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347Standard EuropeKatakanaPC850Multilingual PC860PortuguesePC863Canadian-FrenchPC865Nordic West EuropeGreekHebrewEast EuropeIranWPC1252PC866Cyrillic#2 PC852Latin2PC858IranIIatvianArabicPT1511251
Barcode types	UPC-A/UPC-E/JAN13EAN13/JAN8EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	
Input buffer	64 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	InputAC 100-240V, 50~60Hz Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.26 KG
Dimensions	185*145*136mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (045) humidity(1080%)
Storage environment	Temperature(-1060) humidity(1080%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS

Driver	Windows/JPOS/Linux/Android/Mac/OPOS
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows