XPRINTER

XP-P322B

Kod: 00-00005608 · Printerlər



Xprinter XP-P322B — termal çap texnologiyasına malik kompakt etiket printeridir. USB və Bluetooth bağlantısı sayəsində həm kompüter, həm də mobil cihazlarla rahat işləyir. Etiket, barkod və qiymət nişanları çapı üçün idealdır. Asan quraşdırma və sabit performans təmin edir.

Texniki göstəricilər

Printer	**Çek**
Növ	Printerin tipi
USB + Bluetooth	
Printer qoşulma	

Ətraflı məlumat

Model	**XP-P322B**
Printing Features	
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	Max. 70mm (2.7") / s
Max.print width	72 mm (2.8")
Max.print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	25.4 mm ~ 76 mm
Media thickness	0.06 mm ~0.16 mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	Stardard version: USB+Bluetooth Optional:USB+WIFI
Screen	OLED (0.96") Resolution: 128*64 pix
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code

Rotation	0°□ 90°□ 180°□ 270°
Emulaion	TSPL□ EPL□ ZPL□ DPL□ CPCL□ ESC/POS
Physical Features	
Dimension	120×112×60mm (D×W×H)
Weight	400 g
Reliability	
Print head life	30 km
Software	
Operation system	Windows/Android/iOS
SDK	Windows/Android/iOS
Power supply	
USB	DC 5V/2A
Battery	2500mAh
Environmental Conditions	
Operation environment	5 ~ 40°C□ 41~104°F□□ Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C□ -40~140°F□□ Humidity: 10 ~ 90% no condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az