

XP-P322B

Xprinter XP-P322B — termal çap texnologiyasına malik kompakt etiket printeridir. USB və Bluetooth bağlantısı sayəsində həm kompüter, həm də mobil cihazlarla rahat işləyir. Etiket, barkod və qiymət nişanları çapı üçün idealdır. Asan quraşdırma və sabit performans təmin edir.



Specifications

Model	XP-P322B
Brand	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qo?ulma	USB + Bluetooth

KEY FEATURES

Model	XP-P322B		
Printing Features			
Resolution	203 DPI		
Printing method	Direct Thermal		
Max.print speed	Max. 70mm (2.7") / s		
Max.print width	72 mm (2.8")		
Max.print length	1778 mm (70")		
Media			
Media type	Continuous, gap, black mark		
Media width	25.4 mm ~ 76 mm		
Media thickness	0.06 mm ~0.16 mm		
Performance Features			
Processor	32-bit CPU		
Memory	8MB Flash Memory/ 8MB SDRAM		
Interface	Stardard version: USB+Bluetooth Optional:USB+WIFI		
Screen	OLED (0.96") Resolution: 128*64 pix		
Sensors	Gap sensor Cover opening sensor Black mark sensor		
Fonts/Graphics/Symbologies			
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.		
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST		
2D bar code	PDF-417, Maxicode, DataMatrix, QR code		
Rotation	0°90°180°270°		
Emulaion	TSPLZPLDPLCPCLESC/POS		
Physical Features			
Dimension	120×112×60mm (D×W×H)		
Weight	400 g		
Reliability			
Print head life	30 km		
Software			
Operation system	Windows/Android/iOS		
SDK	Windows/Android/iOS		
Power supply			
USB	DC 5V/2A		
Battery	2500mAh		
Environmental Conditions			
Operation environment	5 ~ 40°C41~104°FHumidity: 25 ~ 85% no condensing		

Storage environment-40 ~ 60°C-40~140°FHumidity: 10 ~ 90% no condensing