

XP-Q833L

XPRINTER XP-Q833L USB+LAN EU POWER PLUG (CEK PRINTER)



Specifications

Model	XP-Q833L
Brand	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoʻulma	USB+LAN

KEY FEATURES

Printing

Printing method	Direct thermal
Media width	79.5±0.5mm / φ 80 mm
Print width	72mm
Column capacity	576 dots/line or 512 dots/line
Printing speed	230mm/s 260mm/s
Interface	USB / USB+Serial / USB+Lan / (Optional: Bluetooth/Wifi) USB+Serial+Lan (Optional: Bluetooth/Wifi)
Line spacing	3.75mm (Adjustable by commands)
Character size	ANK Font A 1.5×3.0mm 12×24 dots Font B 1.1×2.1mm 9×17 dots Chinese,traditional Chinese:3.0×3.0mm 24×24 dots
Barcode Character	
Extension character sheet	PC347 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranI Latvian Arabic PT151 1251
1D Barcode	UPC-A/UPC-E/JAN13 EAN13/JAN8 EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE: Lan / USB+Lan QR CODE / PDF417
Input buffer	128 Kbytes: USB+Serial / USB / USB+Bluetooth/USB+WiFi 256 Kbytes: Lan / USB+Lan / USB+Serial+Lan
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100V/240V, 50/60Hz; Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	0.87 KG
Dimensions	180*145*130mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0/45) humidity(10/80%)
Storage environment	Temperature(-10/60) humidity(10/90%)
Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC / POS
Driver	Windows / Linux / Mac OS / Android