XPRINTER

XP-Q851L

Kod: 00-00005638 · Printerlər



Xprinter XP-Q851L yüksək performanslı termal reçipt printeridir. ESC/POS əmr emulyasiyasını dəstəkləyir, avtomatik kəsici var və USB / LAN / Serial (opsional) bağlantıları mümkündür. 80 mm rulon kağızı dəstəkləyir və 1.5 milyon kəsik ömrünə malikdir.

Texniki göstəricilər

Printer	Növ
Çek	Printerin tipi
USB+LAN	Printer qoşulma

Ətraflı məlumat

Printing	
Printing method	Direct thermal
Media width	79.5±0.5mm / φ 80 mm
Print width	72mm
Column capacity	576 dots/line or 512 dots/line
Printing speed	230mm/s
Interface	USB / Lan / USB+Serial / USB+Lan (Optional:USB+Bluetooth / USB+WiFi)
Line spacing	3.75mm (Adjustable by commands)
Character size	ANK Font A 1.5×3.0mm 12×24 dots Font B 1.1×2.1mm 9×17 dots Chinese,traditional Chinese:3.0×3.0mm 24×24 dots
Barcode Character	
Extension character sheet	PC437 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 IranII Latvian Arabic PT151 1251
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR code / PDF417
Input buffer	64 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100/240V, 50 60Hz
Printer input	DC 24V/2.0A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	1.12 KG
Dimensions	176.8 6* 144.5 * 136.3mm(D*W*H)
Environmental Requirements	

Work environment	Temperature (0□ 45℃) humidity(10□ 80%)
Storage environment	Temperature(-10□ 60℃) humidity(10□ 90%)
Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC / POS
Driver	Windows / Linux / Mac OS / Android

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az