

XP-Q890K

Xprinter XP-Q890K yüksək sürətli termal recib printeridir. 203 DPI qətnamə və 230 mm/s çap sürəti ilə POS sistemləri üçün idealdır. USB və LAN interfeysləri, avtomatik kəsici, ESC/POS dəstəyi, 80 mm və 58 mm kağız eni variantları ilə çox yönlüdür. Güc adaptoru AC 100-240 V (EU) + çıxış DC 24V / 2.5A.



Specifications

Model	XP-Q890K
Brand	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoşulma	USB+LAN

KEY FEATURES

Model	XP-Q890K
Resolution	203 DPI
Printing method	Direct thermal
Paper width	80mm / 58mm
Print width	72mm / 48mm
Column capacity	576 dots/line
Printing speed	230 mm/s
Interface	USB / USB+Serial / USB+Lan
Line spacing	3.75mm(Adjustable by commands)
Character size	ANK 1.5×3.0mm 12×24 dots Font B 1.1×2.1mm 9×17 dots Chinese, traditional Chinese:3.0×3.0mm 24×24 dots
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic)/West Europe / Greek / Hebrew / East Europe/Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)
Barcode types	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Barcode	QR Code / PDF417
Input buffer	96 Kbytes(USB, USB+Serial); 256 Kbytes(USB+Lan)
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100-240V / 50~60Hz; Output :DC 24V/2.5A
Printer input	DC 24V / 2.5A
Cash drawer	DC 24V / 1A
Physical characteristics	
Weight	1 KG
Dimensions	165 × 125 × 110mm(D*W*H)
Environmental Requirements	
Work environment	Temperature (0~45); humidity(10~80%)
Storage environment	Temperature(-10~60); humidity(10~90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS
Driver	Windows / Linux / Mac OS / Android