

XP-S200M

XPRINTER XP-S200M USB+LAN EU POWER PLUG (CEK PRINTER)



Specifications

Model	XP-S200M
Brand	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoʻulma	USB+LAN

KEY FEATURES

Model	XP-S200M	XP-S260M	XP-S300M
Printing			
Printing method	Direct thermal		
Paper width	79.5±0.5mm		
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm		
Column capacity	576 dots/line(adjustable by command)		
Printing speed	200 mm/s Max.	260 mm/s Max.	300 mm/s Max.
Interface	USB(Optional :WIFI+Bluetooth)	USB+Serial+Lan	USB+Serial+Lan
	Lan/ USB+Serial	USB+Serial+Lan+Bluetooth	
	USB+Lan(Optional :WIFI+Bluetooth)	USB+Serial+Lan+WIFI	
Line spacing	3.75mm (Adjustable by commands)		
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns		
Character size	ANK:Font A:1.5×3.0mm:12×24 dots:Font B:1.1×2.1mm:9×17 dots:Chinese,traditional Chinese:3.0×3.0mm:24×24 dots		
Cutter			
Auto cutter	Partial		
Barcode Character			
Extension character sheet	PC347:Standard Europe:Katakana:PC850:Multilingual:PC860:Portuguese:PC863:Canadian-French:PC865:Nordic:West Europe:Greek:Hebrew:East Europe:Iran:WPC1252:PC866:Cyrillic#2:PC852:Latin2:PC858:IranII:Latvian:Arabic:PT151:1251		
Barcode types	UPC-A/UPC-E/JAN13:EAN13/JAN8:EAN8/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417 (Unavailable in interfaces: USB+Serial / USB+WiFi / USB+Bluetooth)		
Input buffer	128 Kbytes	128 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	256 Kbytes	256 Kbytes
Power			
Power adaptor	Input:AC 110V/240V:50~60Hz Output: DC 24V/2.5A		
Printer Input	DC 24V/2.5A		
Cash drawer output	DC 24V/1A		
Physical characteristics			
Weight	0.97 Kg		
Dimensions	180×140×134.1mm (D×W×H)		
Environmental Requirements			
Work environment	Temperature (0~45) humidity:10~80% RH		
Storage environment	Temperature -10~60 humidity:10~90% RH		
Reliability			
Cutter life	1.5 million cuts		
Printer head life	150 KM		
Software			
Emulation	ESC/POS		

Driver	Windows/JPOS/ OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows