

XP-S200M

XPRINTER XP-S200M USB+LAN EU POWER PLUG (CEK PRINTER)



Model	XP-S200M
Brend	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoşulma	USB+LAN

Specification

Model	XP-S200M	XP-S260M	XP-S300M
Printing			
Printing method	Direct thermal		
Paper width	79.5±0.5mm		
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm		
Column capacity	576 dots/line(adjustable by command)		
Printing speed	200 mm/s Max.	260 mm/s Max.	300 mm/s Max.
Interface	USB(Optional :WiFi+Bluetooth) Lan/ USB+Serial USB+Lan(Optional :WiFi+Bluetooth)	USB+Serial+Lan USB+Serial+Lan+Bluetooth USB+Serial+Lan+WIFI	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)		
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns		
Character size	ANK Font A: 1.5×3.0mm 12×24 dots Font B: 1.1×2.1mm 9×17 dots Chinese,traditional Chinese:3.0×3.0mm 24×24 dots		
Cutter			
Auto cutter	Partial		
Barcode Character			
Extension character sheet	PC347 Standard Europe Katakana PC850 Multilingual PC860 Portuguese PC863 Canadian-French PC865 Nordic West Europe Greek Hebrew East Europe Iran WPC1252 PC866 Cyrillic#2 PC852 Latin2 PC858 Iran Latvian Arabic PT151 1251		
Barcode types	UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128		
2D Barcode	QR CODE / PDF417 (Unavailable in interfaces: USB+Serial / USB+WIFI / USB+Bluetooth)		
Input buffer	128 Kbytes	128 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	256 Kbytes	256 Kbytes
Power			

Power adaptor	Input: AC 110V/240V 50~60Hz Output: DC 24V/2.5A
Printer Input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	0.97 Kg
Dimensions	180×140×134.1mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45°C) humidity:10~80% RH
Storage environment	Temperature -10~60°C humidity:10~90% RH
Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/ OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows