

XVR301-04Q3

XVR301-04Q3 series 4CH Digital Video Recorder UNV

| | |
|---------------|-------------|
| Model | XVR301-04Q3 |
| Brend | Uniview |
| Növ | XVR |
| Kanal sayı | 4 kanal |
| Meqapixel | 8 MP |
| Max HDD sayı | 1 HDD |
| Max HDD həcmi | 8 TB |



Specification

| Model | XVR301-04Q3 | XVR301-08Q3 |
|-------------------------------|---|---|
| Video/Audio Input | | |
| Analog Video Input | 4-ch, BNC | 8-ch, BNC |
| IP Video Input | 2-ch(only IP up to 6ch), each channel up to 4MP | 4-ch(only IP up to 12ch), each channel up to 8MP |
| Supported Analog Camera Types | Support AHD input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support TVI input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVI input: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input | Support AHD input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support TVI input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVI input: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input |
| Audio Input | 1-ch, RCA | |
| Audio Compression | G.711U | |
| Video/Audio Output | | |
| CVBS Output | 1-ch, BNC | |
| VGA Output | 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz | |
| HDMI Output | 3840 x 2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz | |
| Audio Output | 1-ch, RCA | |
| Synchronous Playback | 4 | 8 |
| Live view display | HDMI/VGA: 1/4/6/8/9 | HDMI/VGA: 1/4/6/8/9/16 |
| Two-way Audio | 1-ch, RCA | |
| Snapshot | | |
| FTP/Schedule/Event Snapshot | 4-ch snapshot, up to 704*576 resolution | 8-ch snapshot, up to 704*576 resolution |
| Network | | |

| | | | | |
|------------------------|---|------------|---|------------|
| Incoming Bandwidth | 40Mbps (Up to 48Mbps after all analog channel conversion) | | 40Mbps (Up to 56Mbps after all analog channel conversion) | |
| Outgoing Bandwidth | 48Mbps | | 64Mbps | |
| Remote Users | 128 | | | |
| Protocols | TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP | | | |
| Browser | IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows | | | |
| Encoding | | | | |
| Recording Resolution | 8MP Lite/5MP Lite/4MP Lite/1080P/720P/CIF | | 8MP Lite/5MP Lite/4MP Lite /1080P/720P/CIF | |
| Recording Frame Rate | Main stream | Sub stream | Main stream | Sub stream |
| | 8MP Lite@8fps | D1@8fps | 8MP Lite@8fps | D1@8fps |
| | 5MP Lite @12fps | D1@12fps | 5MP Lite @12fps | D1@12fps |
| | 4MP Lite@15fps | D1@15fps | 4MP Lite@15fps | D1@15fps |
| | 1080P@15fps | D1@15fps | 1080P@15fps | D1@15fps |
| 720p@30fps | D1@30fps | 720p@30fps | D1@30fps | |
| Audio Sample Rate | 8KHz, 16 bit per channel | | | |
| Audio Bit Rate | 64Kbps per channel | | | |
| Decoding | | | | |
| Capability | Analog: 4 x 8MP Lite@8, 4x 5MP Lite@12, 4x 4MP Lite@15, 4 x 1080P@15 IP: 1 x 4MP@30, 2 x 1080P@30 | | Analog: 8 x 8MP Lite@8, 8x 5MP Lite@12, 8x 4MP Lite@15, 8x 1080P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30 | |
| Hard Disk | | | | |
| SATA | 1 SATA interface | | | |
| Capacity | Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature) | | | |
| Smart Alarm | | | | |
| VCA Detection | Ultra Motion Detection(UMD) for analog:4-ch | | Ultra Motion Detection(UMD) for analog:8-ch | |
| VCA Search | Behavior Search | | | |
| General Alarm | | | | |
| General Alarm | Motion detection | | | |
| Alert Alarm | IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal | | | |
| External Interface | | | | |
| Network Interface | 1 RJ45 10M/100M self-adaptive Ethernet Interface | | | |
| USB Interface | Rear panel: 2 x USB2.0 | | | |
| RS485 | 1 | | | |
| Alarm In | 4-ch | | | |
| Alarm Out | 1-ch | | | |
| General | | | | |
| Power Supply | 12V DC Power Consumption: ≤ 10 W(without HDD) | | | |
| Working Environment | -10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing) | | | |
| Dimensions(W×D×H) | 260mm ×226mm× 47mm (10.2" × 8.9"×1.8") | | | |
| Weight (without HDD) | ≤1.1 Kg (2.42lb) | | | |
| Certification | | | | |
| Certification | UL /CE /FCC /RoHS /WEEE | | | |