eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

UNIVIEW

XVR301-08F

Kod: 00-00003882 · Videoregistrator



XVR301-08F series 8CH Digital Video Recorder UNV

Texniki göstəricilər

XVR Növ	**8 kanal** Kanal sayı
2 MP Meqapixel	**1 HDD** Max HDD sayı
6 TB Max HDD həcmi	

Ətraflı məlumat

Model	XVR301-04F	XVR301-08F
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch), each channel up to 6MP	2-ch(only IP up to 10ch), each channel up to 6MP
Supported Analog Camera Types	**Support AHD input:** 1080P@30fps 720P@30fps **Support TVI input:** 1080P@30fps 720P@30fps **Support CVI input:** 1080P@30fps 720P@30fps **Support CVBS input**	**Support AHD input:** 1080P@30fps 720P@30fps **Support TVI input:** 1080P@30fps 720P@30fps **Support CVI input:** 1080P@30fps 720P@30fps **Support CVBS input**
Audio Compression	G.711U	
Video/Audio Output		
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Synchronous Playback	HD:4-ch SD:4-ch	HD:8-ch SD:8-ch
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16
Network		
Incoming Bandwidth	24Mbps (Up to 32Mbps after all analog channel conversion)	24Mbps (Up to 40Mbps after all analog channel conversion)
Outgoing Bandwidth	48Mbps	64Mbps
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP	
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	

Encoding				
Recording Resolution	1080P Lite/720P/D1		1080P Lite/720P/D1	
Recording Frame Rate	**Main stream**	**Sub stream**	**Main stream**	**Sub stream**
	1080P Lite@25fps	D1@25fps	1080P Lite@15fps	D1@12fps
	720P@30fps	D1@30fps	720P@15fps	D1@15fps
Audio Sample Rate	8KHz,16 bit per channel			
Audio Bit Rate	64Kbps per channel			
Decoding				
Capability	Analog:4 x 1080P Lite@25, 4 x 720P@30 IP: 1 x 6MP@20, 2 x 1080P@30		Analog:8x 1080P Lite @15, 8x 720P @15 IP: 1 x 6MP@20, 2 x 1080P@30	
Hard Disk				
SATA	1 SATA interface			
Capacity	Up to 6TB for each HDD			
General Alarm				
General Alarm	Motion detection			
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal			
External Interface				
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface			
USB Interface	Rear panel: 2 x USB2.0			
General				
Power Supply	12V DC Power Consumption: ≤ 10 W(without HDD)			
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)			
Dimensions(W×D×H)	190mm × 202mm × 42mm (7.5" × 7.9" × 1.6")			
Weight (without HDD)	≤0.6 Kg (1.32lb)			
Certification				

Certification	UL/CE/FCC /RoHS /WEEE

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az