

# XVR301-08F

XVR301-08F series 8CH Digital Video Recorder UNV



## Specifications

Model	XVR301-08F
Brand	Uniview
Növ	XVR
Kanal say?	8 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

## KEY FEATURES

Model	XVR301-04F	XVR301-08F
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch), each channel up to 6MP	2-ch(only IP up to 10ch), each channel up to 6MP
Supported Analog Camera Types	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input
Audio Compression	G.711U	
Video/Audio Output		
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Synchronous Playback	HD:4-ch SD:4-ch	HD:8-ch SD:8-ch
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16
Network		
Incoming Bandwidth	24Mbps (Up to 32Mbps after all analog channel conversion)	24Mbps (Up to 40Mbps after all analog channel conversion)
Outgoing Bandwidth	48Mbps	64Mbps
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP	
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	
Encoding		
Recording Resolution	1080P Lite/720P/D1	1080P Lite/720P/D1
Recording	Main stream      Sub stream	Main stream      Sub stream
Frame Rate	1080P Lite@25fps      D1@25fps	1080P Lite@15fps      D1@12fps
	720P@30fps      D1@30fps	720P@15fps      D1@15fps
Audio Sample Rate	8KHz, 16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Decoding		
Capability	Analog:4 x 1080P Lite@25, 4 x 720P@30 IP: 1 x 6MP@20, 2 x 1080P@30	Analog:8x 1080P Lite @15, 8x 720P @15 IP: 1 x 6MP@20, 2 x 1080P@30
Hard Disk		
SATA	1 SATA interface	
Capacity	Up to 6TB for each HDD	
General Alarm		
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	

---

**External Interface****Network Interface** 1 RJ45 10M/100M self-adaptive Ethernet Interface**USB Interface** Rear panel: 2 x USB2.0**General****Power Supply** 12V DC

Power Consumption: ≤ 10 W( without HDD )

**Working Environment** -10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)**Dimensions(W×D×H)** 190mm × 202mm × 42mm (7.5" × 7.9" × 1.6")**Weight ( without HDD )** ≤0.6 Kg ( 1.32lb )**Certification****Certification** UL/CE/FCC /RoHS /WEEE