

# XVR301-08F

## XVR301-08F series 8CH Digital Video Recorder UNV



Model	XVR301-08F
Brend	Uniview
Növ	XVR
Kanal sayı	8 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB

## Specification

Model	XVR301-04F	XVR301-08F		
Video/Audio Input				
Analog Video Input	4-ch, BNC	8-ch, BNC		
IP Video Input	2-ch(only IP up to 6ch), each channel up to 6MP	2-ch(only IP up to 10ch), each channel up to 6MP		
Supported Analog Camera Types	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input	Support AHD input: 1080P@30fps 720P@30fps Support TVI input: 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input		
Audio Compression	G.711U			
Video/Audio Output				
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz			
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz			
Synchronous Playback	HD:4-ch SD:4-ch	HD:8-ch SD:8-ch		
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16		
Network				
Incoming Bandwidth	24Mbps (Up to 32Mbps after all analog channel conversion)	24Mbps (Up to 40Mbps after all analog channel conversion)		
Outgoing Bandwidth	48Mbps	64Mbps		
Remote Users	128			
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP			
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows			
Encoding				
Recording Resolution	1080P Lite/720P/D1	1080P Lite/720P/D1		
Recording Frame Rate	Main stream 1080P Lite@25fps	Sub stream D1@25fps	Main stream 1080P Lite@15fps	Sub stream D1@12fps

720P@30fps	D1@30fps	720P@15fps	D1@15fps
Audio Sample Rate	8KHz, 16 bit per channel		
Audio Bit Rate	64Kbps per channel		
Decoding			
Capability	Analog: 4 x 1080P Lite@25, 4 x 720P@30 IP: 1 x 6MP@20, 2 x 1080P@30	Analog: 8x 1080P Lite @15, 8x 720P @15 IP: 1 x 6MP@20, 2 x 1080P@30	
Hard Disk			
SATA	1 SATA interface		
Capacity	Up to 6TB for each HDD		
General Alarm			
General Alarm	Motion detection		
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal		
External Interface			
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface		
USB Interface	Rear panel: 2 x USB2.0		
General			
Power Supply	12V DC Power Consumption: ≤ 10 W( without HDD )		
Working Environment	-10°C ~ +55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)		
Dimensions(W×D×H)	190mm × 202mm × 42mm ( 7.5" × 7.9" × 1.6" )		
Weight ( without HDD )	≤0.6 Kg ( 1.32lb )		
Certification			
Certification	UL/CE/FCC /RoHS /WEEE		