UNIVIEW

XVR301-08G3

Kod: 00-00003595 · Videoregistrator



XVR301-08G3 series 8ch Digital Video Recorder UNV

Texniki göstəricilər

XVR	**8 kanal**
Növ	Kanal sayı
5 MP	**1 HDD**
Meqapixel	Max HDD sayı
8 TB	
Max HDD həcmi	

Ətraflı məlumat

Model	XVR301-04G3	XVR301-08G3
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch), each channel up to 4MP	4-ch(only IP up to 8ch), each channel up to 4MP
Supported Analog Camera Types	**Support AHD input:** 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support TVI input:** 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVI input:** 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVBS input**	**Support AHD input:** 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps **Support TVI input:** 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps **Support CVI input:** 1080P@30fps 720P@30fps **Support CVBS input**
Audio Input	1-ch, RCA	
Audio Compression	G.711U	
Video/Audio Output		
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Audio Output	1-ch, RCA	
Synchronous Playback	HD:2-ch SD:4-ch	HD:4-ch SD:8-ch
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16
Two-way Audio	1-ch, RCA	
Snapshot		

FTP/Schedule/Event Snapshot	Schedule snapshot is not supported 4-ch snapshot, up to 704*576 resolution		Schedule snapshot is not supported 8-ch snapshot, up to 704*576 resolution	
Network				
Incoming Bandwidth	16Mbps (Up to 24Mbps after all analog channel conversion)		32Mbps (Up to 40Mbps after all analog channel conversion)	
Outgoing Bandwidth	48Mbps		64Mbps	
Remote Users	128			
Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP			
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows			
Encoding				
Recording Resolution	5MP Lite/4MP Lite/1080P/720P/CIF		5MP Lite/4MP Lite /1080P Lite/720P/CIF	
Recording Frame Rate	**Main stream:**	**Sub stream:**	**Main stream:**	**Sub stream:**
	5MP Lite@12fps	D1@12fps	5MP Lite@6fps	D1@6fps
	4MP Lite@15fps	D1@15fps	4MP Lite@8fps	D1@8fps
	1080P@15fps	D1@15fps	1080P Lite@12fps	D1@12fps
	720P@25fps	D1@25fps	720P@12fps	D1@12fps
Audio Sample Rate	8KHz,16 bit per channel			
Audio Bit Rate	64Kbps per channel			
Decoding				
Capability	Analog: 2 x 5MP Lite@12, 2 x 4MP Lite@15, 2 x 1080P@15 IP: 1 x 4MP@30, 2 x 1080P@30		Analog: 4 x 5MP Lite@6,4x 4MP Lite@8, 4x 1080P Lite @12fps IP: 1 x 4MP@30, 2 x 1080P@30	
Hard Disk				
SATA	1 SATA interface			
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)			
Smart Alarm				

VCA Detection	Ultra Motion Detection(UMD) for analog:4-ch
VCA Search	Behavior Search
General Alarm	
General Alarm	Motion detection
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 8 W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions(W×D×H)	260mm ×226mm× 47mm (10.2" × 8.9"×1.8")
Weight (without HDD)	≤1.1 Kg (2.42lb)
Certification	
Certification	UL CE FCC RoHS WEEE

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az