eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

UNIVIEW

XVR301-08Q3

Kod: 00-00006066 · Videoregistrator



XVR301-08Q3 series 8CH Digital Video Recorder UNV

Texniki göstəricilər

XVR Növ	**8 kanal** Kanal sayı
8 MP Meqapixel	**1 HDD** Max HDD sayı
8 TB Max HDD həcmi	

Ətraflı məlumat

Model	XVR301-04Q3	XVR301-08Q3
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch), each channel up to 4MP	4-ch(only IP up to 12ch), each channel up to 8MP
Supported Analog Camera Types	**Support AHD input:** 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support TVI input:** 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVI input:** 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVBS input**	**Support AHD input:** 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support TVI input:** 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVI input:** 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVBS input**
Audio Input	1-ch, RCA	
Audio Compression	G.711U	
Video/Audio Output		
CVBS Output	1-ch, BNC	
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	3840 x 2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Audio Output	1-ch, RCA	
Synchronous Playback	4	8
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16

Two-way Audio	1-ch, RCA			
Snapshot				
FTP/Schedule/Event Snapshot	4-ch snapshot, up to 704*576 resolution		8-ch snapshot, up to 704*576 resolution	
Network				
Incoming Bandwidth	40Mbps (Up to 48Mbps after all analog channel conversion)		40Mbps (Up to 56Mbps after all analog channel conversion)	
Outgoing Bandwidth	48Mbps		64Mbps	
Remote Users	128			
Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP			
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows			
Encoding				
Recording Resolution	8MP Lite/5MP Lite/4MP Lite/1080P/720P/CIF		8MP Lite/5MP Lite/4MP Lite /1080P/720P/CIF	
Recording Frame Rate	**Main stream**	**Sub stream**	**Main stream**	**Sub stream**
	8MP Lite@8fps	D1@8fps	8MP Lite@8fps	D1@8fps
	5MP Lite @12fps	D1@12fps	5MP Lite @12fps	D1@12fps
	4MP Lite@15fps	D1@15fps	4MP Lite@15fps	D1@15fps
	1080P@15fps	D1@15fps	1080P@15fps	D1@15fps
720p@30fps	D1@30fps	720p@30fps	D1@30fps	
Audio Sample Rate	8KHz,16 bit per channel			
Audio Bit Rate	64Kbps per channel			
Decoding				
Capability	Analog: 4 x 8MP Lite@8, 4x 5MP Lite@12, 4x 4MP Lite@15, 4 x 1080P@15 IP: 1 x 4MP@30, 2 x 1080P@30		Analog: 8 x 8MP Lite@8, 8x 5MP Lite@12, 8x 4MP Lite@15, 8x 1080P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30	
Hard Disk				

SATA	1 SATA interface	
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)	
Smart Alarm		
VCA Detection	Ultra Motion Detection(UMD) for analog:4-ch	Ultra Motion Detection(UMD) for analog:8-ch
VCA Search	Behavior Search	
General Alarm		
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	
External Interface		
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 2 x USB2.0	
RS485	1	
Alarm In	4-ch	
Alarm Out	1-ch	
General		
Power Supply	12V DC Power Consumption: ≤ 10 W(without HDD)	
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)	
Dimensions(W×D×H)	260mm ×226mm× 47mm (10.2" × 8.9"×1.8")	
Weight (without HDD)	≤1.1 Kg (2.42lb)	
Certification		
Certification	UL /CE /FCC /RoHS /WEEE	

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az