eurotech
Taste of technology

TEXNIKI SƏNƏD

13.11.2026

UNIVIEW

XVR301-16F

Kod: 00-00004634 · Videoregistrator



XVR UNIVIEW XVR301-16F 16CH DIGITAL VIDEO RECORDER

Texniki göstəricilər

XVR	Növ
16 kanal	Kanal sayı
2 MP	Meqapixel
1 HDD	Max HDD sayı
6 TB	Max HDD həcmi

Ətraflı məlumat

Model	**XVR301-16F**
Video/Audio Input	
Analog Video Input	16-ch, BNC
IP Video Input	2-ch(only IP up to 18ch), each channel up to 8MP
Supported Analog Camera Types	**Support AHD input:** 1080P@30fps 720P@30fps **Support TVI input:** 1080P@30fps 720P@30fps **Support CVI input:** 1080P@30fps 720P@30fps **Support CVBS input**
Audio Compression	G.711U
Video/Audio Output	
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Synchronous Playback	HD:16-ch SD:16-ch
Live view display	HDMI/VGA: 1/4/6/8/9/16/25
Snapshot	
FTP/Schedule/Event Snapshot	Schedule snapshot is not supported 16-ch snapshot, up to 704*576 resolution
Network	
Incoming Bandwidth	24Mbps (Up to 56Mbps after all analog channel conversion)
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP

Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	
Encoding		
Recording Resolution	1080P Lite/720P/D1	
Recording Frame Rate	**Main stream**	**Sub stream**
	1080P Lite@12fps	D1@12fps
	720P@15fps	D1@15fps
Audio Sample Rate	8KHz,16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Decoding		
Capability	Analog:16x 1080P Lite@12, 16x 720P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30, 8 x 720P@30,16 x D1@30	
Hard Disk		
SATA	1 SATA interface	
Capacity	Up to 6TB for each HDD	
Smart Alarm		
VCA Detection	Ultra Motion Detection(UMD) for analog:8-ch	
VCA Search	Behavior Search	
General Alarm		
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	
External Interface		
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 2 x USB2.0	
General		
Power Supply	12V DC Power Consumption: ≤ 10 W(without HDD)	

Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions(W×D×H)	253mm × 212mm × 42mm (10.0" × 8.4" × 1.7")
Weight (without HDD)	≤0.85 Kg (1.87lb)
Certification	
Certification	UL/CE/FCC /RoHS /WEEE

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az