

# XVR301-16G3

## XVR301-16G3 series 16CH Digital Video Recorder UNV

Model	XVR301-16G3
Brend	Uniview
Növ	XVR
Kanal sayı	16 kanal
Meqapixel	5 MP
Max HDD sayı	1 HDD
Max HDD həcmi	8 TB



## Specification

Model	XVR301-16G3
Video/Audio Input	
Analog Video Input	16-ch, BNC
IP Video Input	8-ch (up to 16-ch after analog camera conversion)
Supported Analog Camera Types	Support AHD input: 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps Support TVI input: 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input
Audio Input	1-ch, RCA
Audio Compression	G.711U
Video/Audio Output	
VGA Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Synchronous Playback	HD: 8-ch SD: 16-ch
Live view display	HDMI/VGA: 1/4/6/8/9/16/25
Two-way Audio	1-ch, RCA
Snapshot	
FTP/Schedule/Event Snapshot	Schedule snapshot is not supported 16-ch snapshot, up to 704*576 resolution
Network	
Incoming Bandwidth	40Mbps (up to 56Mbps after all analog camera conversion)
Outgoing Bandwidth	64Mbps
Remote Users	128

Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP	
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	
Recording Resolution	5MP Lite/4MP Lite /1080P Lite/720P/D1/CIF	
Recording Frame Rate	Main stream:	Sub stream:
	5MP Lite@6fps	D1@6fps
	4MP Lite@8fps	D1@8fps
	1080P Lite@12fps	D1@12fps
	720P@12fps	D1@12fps
Audio Sample Rate	8KHz,16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Decoding		
Capability	Analog: 8 x 5MP Lite@6, 8 x 4MP Lite@8, 8 x 1080P Lite@12 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30	
Hard Disk		
SATA	1 SATA interface	
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)	
Smart Alarm		
VCA Detection	Ultra Motion Detection(UMD) for analog:8-ch	
VCA Search	Behavior Search	
General Alarm		
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	
External Interface		
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 2 x USB2.0	
Serial Interface	1 x RS485	
General		
Power Supply	12V DC Power Consumption: ≤ 10 W( without HDD )	
Working Environment	-10°C ~ +55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)	
Dimensions(W×D×H)	260mm ×226mm× 47mm (10.2" × 8.9"×1.8")	
Weight ( without HDD )	≤1.1 Kg ( 2.42lb )	
Certification		
Certification	UL CE FCC RoHS WEEE	