eurotech
Taste of technology

**TEXNIKI SƏNƏD**

13.11.2026

UNIVIEW

# XVR302-32Q3

Kod: 00-00004633 · Videoregistrator



XVR UNIVIEW XVR302-32Q3 32CH 2HDD (Up to 8TB )

## Texniki göstəricilər

| | |
|---|---|
| **XVR** | Növ |
| **32 kanal** | Kanal sayı |
| **8 MP** | Meqapixel |
| **2 HDD** | Max HDD sayı |
| **8 TB** | Max HDD həcmi |

## Ətraflı məlumat

| Video/Audio Input | Description |
|---|---|
| IP Video Input | 4-ch |
| Analog Video Input | 32-ch, BNC |
| Max IP Video Input | 36-ch |
| Supported Analog Camera Types | Support AHD input:<br>8MP@15fps<br>5MP@20fps<br>4MP@30fps<br>1080P@30fps<br>720P@30fps<br>Support TVI input:<br>8MP@15fps<br>5MP@20fps<br>4MP@30fps<br>1080P@30fps<br>720P@30fps<br>Support CVI input:<br>8MP@15fps<br>5MP@25fps<br>4MP@30fps<br>1080P@30fps<br>720P@30fps<br>Support CVBS input |
| BNC Audio Input | 32-ch, channel audio |
| RCA Audio Input | 1-ch |
| **Video/Audio Output** | **Description** |
| HDMI Output | HDMI:4K(3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| VGA Output | VGA:<br>1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| BNC Video Output | 1-ch |
| RCA Audio Output | 1-ch |

| | |
|---|---|
| Live View Display | HDMI/VGA: 1/4/6/8/9/25/36 |
| **Encoding/Decoding** | **Description** |
| Recording Resolution | 8MP Lite/5MP Lite/4MP Lite /1080P/720P/D1 |
| Recording Frame Rate | Main stream: 8MP Lite@8fps  Sub stream: D1@8fps<br>Main stream: 5MP Lite@12fps  Sub stream: D1@12fps<br>Main stream: 4MP Lite@15fps  Sub stream: D1@15fps<br>Main stream: 1080P@15fps  Sub stream: D1@15fps<br>Main stream: 720P@30fps Sub stream: D1@30fps |
| Audio Sample Rate | 8KHz,16 bit per channel |
| Audio Bit Rate | 64Kbps per channel |
| Decoding Capability | Analog: 16 x 8MP Lite@8, 16 x 5MP Lite@12, 16 x 4MP Lite@15, 16 x 1080P@15, 16 x 720@30<br>IP: 16 x 720P@30, 8 x 1080P@30, 4 x 4MP@30, 2 x 8MP@30 |
| Num of Concurrent Playback in Local | 16-ch |
| **Coaxial Cable** | **Description** |
| Audio over Coaxial Cable(Form) | 32-ch, One-way Audio(only for Uniview CVI protocol cameras) |
| **Two-way Audio** | **Description** |
| Two-way Audio | 1-ch, RCA(Using the audio input and output) |
| **Analog Snapshot** | **Description** |
| FTP/Schedule/Event Snapshot | Schedule/FTP/Event snapshot:32-ch snapshot, up to 704*576 resolution |
| **Network** | **Description** |
| Incoming Bandwidth | 80Mbps (Up to 144Mbps after all analog channel conversion) |
| Outgoing Bandwidth | 160Mbps |
| Remote Users | 128 |
| Protocols | TCP/IP;P2P;UPnP;DHCP;HTTP;HTTPS;DNS;DDNS;SMTP;NTP |
| Browser(Plugin) | Windows:IE(IE10/11),Firefox (version 52.0 and above),Chrome(version 45 and above),Edge(version 79 and above) |
| **Smart** | **Description** |
| Analog Smart by XVR | SIP(Intrusion Detection,Cross Line Detection,Enter Area,Leave Area);Ultra Motion Detection(UMD) |

| | |
|---|---|
| IP Smart by IPC | Face Detection;SIP(Intrusion Detection,Cross Line Detection,Enter Area,Leave Area);Defocus Detection;Scene Change Detection;Object Removed;Object Left Behind;Auto Tracking |
| VCA Search | Face Search;Behavior Search |
| Smart Functions by XVR | 16-ch(UMD), 8-ch(SIP) |
| **Alarm** | **Description** |
| General Alarm | Motion |
| Alert Alarm | IP Conflict;Network Disconnected;Disk offline;Disk Abnormal;Illegal Access;Hard Disk Space Low;Hard Disk Full;Recording/Snapshot Abnormal |
| **Hard Disk** | **Description** |
| SATA | 2 SATA interfaces |
| Capacity | Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature) |
| **External Interface** | **Description** |
| Network Interface | 1 RJ45 10M/100M/1000M  self-adaptive Ethernet Interface |
| USB | Rear panel: 1 x USB3.0;Front panel: 1 x USB2.0 |
| RS485 | 1 |
| Alarm In | 4-ch |
| Alarm Out | 1-ch |
| Power Supply | DC 12V/5A |
| **Working Environment** | **Description** |
| Working Temperature | -10°C ~ + 55°C ( +14°F ~ +131°F ) |
| Working Humidity | ≤ 90% RH(non-condensing) |
| Power Consumption (without HDD) | ≤ 38W |
| **Dimensions** | **Description** |
| Weight (without HDD) | ≤2.6 Kg ( 5.72lb ) |
| Dimensions | 380mm ×326mm× 53mm (15.0" × 12.8"×2.1") |
| **Certification** | **Description** |
| Certification | CE, FCC, UL, RoHS, WEEE |

| | |
|---|---|
| CE | EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035 |
| FCC | Part15 Subpart B |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az