

XVR5232AN-I3

Dahua XVR5232AN-I3 32 kanal xvr, 5 meqapiksel, 2 HDD, maks 16 TB HDD həcmi. 32 kanala qədər IP kamera girişləri və hər bir kanal 6 MP-ə qədər dəstəkləyir. Maksimum 128 Mbps daxil olan bant genişliyi. WizSense 2 kanal üz tanıma, 2 kanal perimetr mühafizəsi, 16 kanal SMD plus



Specifications

Model	XVR5232AN-I3
Brand	Dahua
Növ	XVR
Kanal say?	32 kanal
Meqapixel	5 MP
Max HDD say?	2 HDD
Max HDD həcmi	16 TB

KEY FEATURES

System

Main Processor Industrial-grade processor

Operating System Embedded Linux

Operating Interface Web; Local GUI

Perimeter Protection

Perimeter Performance AI by Recorder Advanced Model: 2 channels, 10 IVS for each channel

(Number of Channels) General Model: 8 channels, 10 IVS for each channel

Face Detection

Face Attributes Gender; age group; glasses; expressions; face mask; beard

Face Detection Performance of AI by Recorder (Number of Channels) 2 channels (up to 12 face images/s each channel)

Face Recognition

Face Database Capacity Up to 10 face databases with 10,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries & regions and state can be added to each face image

Face Recognition Performance of AI by 2 channels

Recorder (Number of Channels)

SMD Plus

SMD Plus by Recorder 16 channels: Secondary filtering for human and motor vehicle , reducing false alarms caused by leaves, rain and lighting condition change

Audio and Video

Analog Camera Input 32 BNC ports, supports HDCVI/AHD/TVI/CVBS auto-detect

Camera Input

1. CVI: 5MP@20fps, 5MP@25fps, 5MP@10/12.5fps, 4MP@25/30fps, 1080p@25/30fps, 720p@50/60fps, 720p@25/30fps.

2. TVI: 5MP@20fps, 4MP@25/30fps, 1080p@25/30fps, 720p@25/30fps.

3. AHD: 5MP@20fps, 4MP@25/30fps, 1080p@25/30fps, 720p@25/30fps.

IP Camera Input

Up to 32 channels of IPC access

32 channels (analog channels are converted to IP channels)

incoming bandwidth: 128 Mbps, recording bandwidth: 128 Mbps and outgoing bandwidth: 128 Mbps

Encoding Capacity

Main stream:

5MP Mode: 4-ch 5MP@(1-6fps); other channels 5M-N@(1-12fps)

5M-N Mode:

All channel 5M-N@(1-12fps);4M-N,1080p@(1-15fps); 1080N, 720p, 960H, D1,CIF@(1-25/30fps)

Sub stream: D1, CIF@(1-15fps)

Dual-stream

Yes

Video Bit Rate

32 kbps-6144 kbps

Audio Sampling

8 kHz, 16 bit

Audio Bit Rate

64 kbps

Video Output

1 HDMI, 1 VGA, 1 TV

VGA: 1920 × 1080, 1280 × 1024, 1280 × 720

HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720

*Simultaneous/heterogeneous video sources output for VGA and HDMI is configurable.

Multi-screen Display	1/4/8/9/16/25/36
Third-party Camera Access	ONVIF; Panasonic; Sony; Axis; Arecont; Samsung
Compression Standard	
Video Compression	AI Coding; Smart H.265+; H.265; Smart H.264+; H.264
Audio Compression	G.711a; G.711u; PCM
Network	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Mobile Phone Access	IOS; Android
Interoperability	ONVIF 22.12(Profile T; Profile S; Profile G); CGI; SDK
Browser	Chrome, IE9 or later, Firefox
Network Mode	Single-address mode
Recording Playback	
Record Mode	General, motion detection; intelligent; alarm; POS
Recording Playback	1/4/9/16
Backup Method	USB device and network
Playback Mode	Instant playback, general playback, event playback, tag playback, smart playback (face and motion detection)
Storage	
Disk Group	Yes
Alarm	
General Alarm	Motion detection; video loss; tampering
Anomaly Alarm	No disk; storage error; disk full; camera offline; IP conflict; MAC conflict
Intelligent Alarm	Face detection; face recognition; perimeter protection
Alarm Linkage	Record; snapshot (panoramic); IPC external alarm output; access controller; voice prompt; buzzer; log; preset; email
Ports	
TV Output	1 channel
Audio Input	1-channel RCA 32-channel BNC (Coaxial Audio)
Audio Output	1-channel RCA
Two-way Talk	Yes (share the same audio input with the first channel)
HDD Interface	2 SATA ports, up to 16TB capacity for each disk. The maximum HDD capacity varies with environment temperature.
RS-485	1 port, for PTZ control
USB	2 (1 front USB 2.0 port, 1 rear USB 3.0 port)
HDMI	1
VGA	1
Network Port	1 (10/100/1000 Mbps Ethernet port, RJ-45)
General	
Power Supply	DC 12V, 5A
Power Consumption	<16 W (without HDD)
Net Weight	1.90 kg (4.20 lb)
Gross Weight	3.20 kg (7.00 lb)
Product Dimensions	375.0 mm × 289.4 mm × 53.0 mm (14.76" × 11.40" × 2.09") (W × D × H)
Packaging Dimensions	433.0 mm × 141.0 mm × 366.0 mm (17.05" × 5.56" × 14.41") (W × D × H)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–90% (RH)

Installation **Rack or desktop**

Certifications

© 2026 Dahua. All rights reserved. | Eurotechnology

CE: CE-LVD: EN 60950-1/IEC 60950-1

CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024