

XVR7416L-4KL-X

Dahua XVR7416L-4KL-X 16 kanal xvr, 8 meqapiksel, 4 HDD, maks 10 TB HDD h?cmi. 32 kanala q?d?r IP kamera giri?l?ri v? h?r bir kanal 12 MP-? q?d?r d?st?kl?yir. Maksimum 128 Mbps daxil olan bant geni?liyi.4 kanal perimetr m?hafiz?si



Specifications

Model	XVR7416L-4KL-X
Brand	Dahua
N?v	XVR
Kanal say?	16 kanal
Meqapixel	8 MP
Max HDD say?	4 HDD
Max HDD h?cmi	10 TB

KEY FEATURES

System

Main Embedded Processor

Processor

Operating Embedded LINUX

System

Video and Audio

Analog 16 Channel, BNC

Camera Input

HDCVI 4K, 6MP, 5MP, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/30fps

Camera

AHD Camera 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps**TVI Camera** 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps**CVBS** PAL/NTSC

Camera

IP Camera 16+16 Channel, each channel up to 12MP

Input

Audio In/Out 4/1, BNC**Two-way** 1 Mic In, 1 Mic Out, BNC

Talk

Recording

Compression H.265+/H.265/H.264+/H.264**Resolution** 4K, 6MP, 5MP, 4MP, 3MP, 4M-N, 1080P, 720P, 960H, D1, CIF

Record Rate

Main stream: 4K(1~7fps); 6MP(1~10fps); 5MP(1~12fps); 4MP/3MP(1~15fps); 4M-N/1080P/720P/960H/D1/CIF(1~25/30fps)**Sub stream:** 960H(1~15fps);

D1/CIF(1~25/30fps)

Bit Rate 32Kbps ~ 8192Kbps Per Channel**Record Mode** Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop**Record** 1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec

Interval

Audio G.711A, G.711U, PCM

Compression

Audio 8KHz, 16 bit Per Channel

Sample Rate

Audio Bit 64Kbps Per Channel

Rate

Display

Interface 2 HDMI, 1 VGA, 1 TV

Resolution

HDMI 1: 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720**HDMI 2 / VGA:** 1920×1080, 1280×1024, 1280×720

Multi-screen Display	When IP extension mode not enabled: 1/4/8/9/16 When IP extension mode enabled: 1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Network	
Interface	1 RJ-45 Port (1000M)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, SNMP, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search (Supports Dahua IP camera, DVR, NVS, etc.)
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 16.12, CGI Conformant
Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis
Alarm input	16
Relay Output	6
Playback and Backup	
Playback	1/4/9/16
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network
Storage	
Internal HDD	4 SATA Ports, up to 10TB capacity for each disk
eSATA	1 Port
Auxiliary Interface	
USB	3 USB Ports (1 USB 2.0 , 2 USB 3.0)
RS232	1 port, for PC communication & Keyboard
RS485	1 Port, for PTZ Control
RS422	1 Port, for PTZ Control
Electrical	
Power Supply	AC100V-240V, 50/60Hz
Power Consumption	<35W
(Without HDD)	
Construction	
Dimensions	1.5U, 440mm×417mm×76mm (17.3" x 16.4" x 3.0")
Net Weight	4.8kg (10.58lb)
(without HDD)	
Gross Weight	7.4kg (16.31lb)
Installation	Desktop installation/Rack-mounted
Environmental	
Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 10%~ 90% RH
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0~ 90% RH